

MODEL NO.	48253C966	REV.:
SERIAL NO.	180902802	
USE CEILING ASSEMBLY	ANY 8330, 8430, 9330, 9430, 8530-750 C/A	
REFRIGERANT CHARGE:		
TYPE	R-410A	
OZS.	10.50	
DESIGN PRESSURES PSIG:		
HIGH SIDE	490	
LOW SIDE	240	

ELECTRICAL RATINGS: SINGLE PHASE			
A/C VOLTS	115	HERTZ	60
COMPR. LRA	50.5	COMPR. BCSC AMPS	11.3
COMPR. RLA	10.0		
USE COMPRESSOR 1450-412		FAN MOTOR H.P.	1/3
		FAN MOTOR FLA	3.4
			13.2
OPTIONAL ELECTRIC HEATER AMPS			

WITHOUT OPTIONAL ELECTRIC HEATER		WITH OPTIONAL ELECTRIC HEATER	
MINIMUM CIRCUIT AMPERAGE	17.5	MINIMUM CIRCUIT AMPERAGE	20.75
MAXIMUM OVERCURRENT PROTECTIVE DEVICE AMPERAGE	20	MAXIMUM OVERCURRENT PROTECTIVE DEVICE AMPERAGE	25
MINIMUM OVERCURRENT PROTECTIVE DEVICE AMPERAGE	20	MINIMUM OVERCURRENT PROTECTIVE DEVICE AMPERAGE	20



ROOM AIR
CONDITIONER
697L

RV PRODUCTS
DIV. OF AIRXCEL® INC. WICHITA, KS

48253C184

MODEL NO. REV.:



48253C966

SERIAL NO.



180902802

1.5 hr Label

MODEL NO.	48253C966	REV.:
SERIAL NO.	180902802	
USE CEILING ASSEMBLY	ANY 8330, 8430, 9330, 9430, 8530-750 C/A	
REFRIGERANT CHARGE:		
TYPE	R-410A	
OZS.	10.50	
DESIGN PRESSURES PSIG:		
HIGH SIDE	490	
LOW SIDE	240	

ELECTRICAL RATINGS: SINGLE PHASE			
A/C VOLTS	115	HERTZ	60
COMPR. LRA	50.5	COMPR. BCSC AMPS	11.3
COMPR. RLA	10.0		
USE COMPRESSOR 1450-412		FAN MOTOR H.P.	1/3
		FAN MOTOR FLA	3.4
			13.2
OPTIONAL ELECTRIC HEATER AMPS			

WITHOUT OPTIONAL ELECTRIC HEATER		WITH OPTIONAL ELECTRIC HEATER	
MINIMUM CIRCUIT AMPERAGE	17.5	MINIMUM CIRCUIT AMPERAGE	20.75
MAXIMUM OVERCURRENT PROTECTIVE DEVICE AMPERAGE	20	MAXIMUM OVERCURRENT PROTECTIVE DEVICE AMPERAGE	25
MINIMUM OVERCURRENT PROTECTIVE DEVICE AMPERAGE	20	MINIMUM OVERCURRENT PROTECTIVE DEVICE AMPERAGE	20



ROOM AIR
CONDITIONER
697L

RV PRODUCTS
DIV. OF AIRXCEL® INC. WICHITA, KS

48253C184

MODEL NO. REV.:



48253C966

SERIAL NO.



180902802

1.5 hr Label