

MODEL NO.	48253C866	REV.: A
SERIAL NO.	190526323	
USE CEILING ASSEMBLY	ANY 8330, 8430, 9330, 9430, 8530-750 C/A	

REFRIGERANT CHARGE:		DESIGN PRESSURES PSIG:	
TYPE	R-410A	HIGH SIDE	500
OZS.	10.25	LOW SIDE	240

ELECTRICAL RATINGS: SINGLE PHASE			
A/C VOLTS	115	HERTZ	60
COMPR. LRA	54.2	COMPR. BCSC AMPS	11.5
COMPR. RLA	10.6		
USE COMPRESSOR		FAN MOTOR H.P.	1/3
1450-420		FAN MOTOR FLA	2.8
		OPTIONAL ELECTRIC HEATER AMPS	13.2

WITHOUT OPTIONAL ELECTRIC HEATER		WITH OPTIONAL ELECTRIC HEATER	
17.2	MINIMUM CIRCUIT AMPERAGE	20	
25	MAXIMUM OVERCURRENT PROTECTIVE DEVICE AMPERAGE	25	
20	MINIMUM OVERCURRENT PROTECTIVE DEVICE AMPERAGE	20	



ROOM AIR
CONDITIONER
697L

RV PRODUCTS
DIV. OF AIRXCEL® INC. WICHITA, KS 48253G180

MODEL NO. REV.: A



48253C866

SERIAL NO.



190526323

RO# 64472
Cust# 50599
Cross